



Circular Inward ø1200 Surface


CD4B-00A9AZDUEF

Benedito Design

Pendant Circular Inward ø1200 Surface LED 63.5W LED warm-white 2400K DALI-2 Gold 1931lm



TECHNICAL FEATURES



Total power consumption of light (W) : 70W

Driver Brand : MEAN WELL

Real lumens : 1931

Voltage / frequency : 100-240V/50-60Hz

Real lm/W : 28

Dimming protocol : DALI-2

Correlated Colour Temperature (CCT) : LED warm-white 2400K

Power Factor : 0.90

Lens / reflector angle : HORIZONTAL 104°

Useful life : 50.000h L80B20

UGR : <=16

Warranty : 5 Years

Structure material : Aluminium


Structure finish : Gold

Diffuser material : Polycarbonate

Diffuser finish : Opal

Smart Compatible

- 71-5961-00-00: Casambi



LUMINOTECHNIC FEATURES

Luminance C0°G65°: 400

Luminance C90°G65°: 397



UGR

UGR crosswise: 14.2

UGR lengthwise: 14.2

Lampholder	Quantity	Light source power (W)
LED	1	63.5W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	14.2
UGR lengthwise	14.2



LOGISTICS

Net weight (kg): 6

Packaged weight (kg): 13

Packaging: 1300mm x 1300mm x 150mm

