




## Dorit Ø140mm


## TC-0349-BLA

Downlight IP44 Dorit Ø140mm LED 14W 3000K Blanco 1149lm

### TECHNICAL FEATURES



Ø140



∠Ø120 0-12mm



120



0-12

Power (W) : 14W

Total power consumption of light (W) : 15.7W

Real lumens : 1149

Real lm/W : 73

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Dimming protocol : ON-OFF

Lens / reflector angle : FLOOD 66°

UGR : <=19

Structure material : Aluminium

Structure finish : Blanco

Diffuser material : Glass

Diffuser finish : Transparent

Voltage / frequency : 100-240V/50-60Hz

Power Factor : 0.90

Useful life : 36.000h L70B30

Warranty : 5 Years

Energy efficiency : LED A++

### LUMINOTECHNIC FEATURES

Light source: LED

Luminance C0°65°: 1932

Luminance 90°65°: 1926

CRI: 80

MacAdam steps: 3



Photobiological risk: RG1

UGR

UGR crosswise: 18.0

UGR lengthwise: 18.0

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	18.0
UGR lengthwise	18.0



### VENTILATION FEATURES

Power used: 15.7W

Service value measurement standard: EN 60879:2019

### LOGISTICS

Net weight (kg): 0.53



Packaged weight (kg): 0.66

Packaging: 155mm x 155mm x 115mm



18 Un

Ø140



95

*B* Ø120  0-12mm