




Ringo Ø110mm

PX-0123-INO

Recessed uplighting IP65/IP67 Ringo Ø110mm LED 2.7W 4000K Stainless steel 229lm



TECHNICAL FEATURES

IP65/IP67 IK10



Power (W) : 2.7W

Total power consumption of light (W) : 3.5W

Real lumens : 229

Real lm/W : 65

Correlated Colour Temperature (CCT) : LED neutral-white 4000K

Dimming protocol : ON-OFF

Lens / reflector angle : SPOT 20°

UGR : <= 16

Structure material : Stainless steel AISI304, Aluminium

Structure finish : Stainless steel

Diffuser material : Glass

Diffuser finish : Transparent

Voltage / frequency : 100-240V/50-60Hz

Useful life : 36.000h L70B30

Warranty : 5 Years

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED LG

Luminance C0°65°: 1083

Luminance 90°65°: 1127

CRI: 80

MacAdam steps: 3



Photobiological risk: RG2

UGR

UGR crosswise: 8.8

UGR lengthwise: 8.7

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	8.8
UGR lengthwise	8.7



VENTILATION FEATURES

Power used: 3.5W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 0.6

Packaged weight (kg): 0.74

Packaging: 115mm x 115mm x 155mm

