


Model Sheet




Optional: Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish	18 Graphite ADAPTA RF 9913 WX
	93 White RAL 9016
LED temperature color	2700 K / 3500 K
Dimming	Push; 1-10V; DALI-2 / Casambi
Installation type	Surface Canopy
Materials	Sphere: Blown glass Glass fastening: Aluminum Diffuser: PC- Polycarbonate Pendant structure: Steel
Light source	5 x LED 3,15W 1050mA F
LED	CRI>80 1562 lm 99 2700 K / 3500 K
Driver	Constant Current 1050 100~240 V V 50~60 Hz HZ
Remarks	Request built-in canopy at www.vibia.com The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the cables.
	<div> <div> <div></div> <div>F</div> <div>Dimmable</div> <div>LED</div> </div> <div> <div>IP20</div> <div>Bi-volt</div> <div>50-60Hz</div> </div> </div>
Application	Hanging lamps
Packaging	2 Box 0.552 m x 0.552 m x 0.18 m Gross weight 8.8 Net weight 4.75 Vol. 0.0548



Lighting effect

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data



Efficiency	49.50%
Coordinate System	CG
Total Flux	1561.40 lm
Maximum Value	141.16 cd/klm

Other Applications

