




Circular Inward 5 Rings (ϕ 1200 ϕ 2000 ϕ 3000 ϕ 2000 ϕ 1200)

CD4E-00A9AZDU05

Benedito Design

Pendant Circular Inward 5 Rings (ϕ 1200 ϕ 2000 ϕ 3000 ϕ 2000 ϕ 1200) LED 494.6W LED warm-white 2400K DALI Black 15481lm



TECHNICAL FEATURES



Total power consumption of light (W) : 505W

Real lumens : 15481

Real lm/W : 31

Correlated Colour Temperature (CCT) : LED warm-white 2400K

UGR : \leq 19

Structure material : Aluminium

Structure finish : Black

Diffuser material : Polycarbonate

Diffuser finish : Opal

Smart Compatible

- 71-5961-00-00: Casambi

Driver Brand : MEANWELL

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : DALI

Power Factor : 0.90

Useful life : 50.000h L80B20

Warranty : 5 Years

LUMINOTECHNIC FEATURES

Luminance C0°G65°: 1068

Luminance C90°G65°: 1058

UGR

UGR crosswise: 17.7

UGR lengthwise: 17.7

Lampholder	Quantity	Light source power (W)
LED	1	494.6W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	17.7
UGR lengthwise	17.7

LOGISTICS

