




## Circular Inward 5 Rings (ø600 ø1200 ø2000 ø1200 ø600)

**CD4F-00A9AZDU05**

Benedito Design

Pendant Circular Inward 5 Rings (ø600 ø1200 ø2000 ø1200 ø600) LED 290.7W LED warm-white 2400K DALI Black 9543lm

### TECHNICAL FEATURES



Total power consumption of light (W) : 296.1W

Real lumens : 9543

Real lm/W : 32

Correlated Colour Temperature (CCT) : LED warm-white 2400K

UGR : <=16

Structure material : Aluminium

Structure finish : Black

Diffuser material : Polycarbonate

Diffuser finish : Opal

Smart Compatible

- 71-5961-00-00: Casambi

Driver Brand : MEAN WELL

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : DALI

Power Factor : 0.90

Useful life : 50.000h L80B20

Warranty : 5 Years

### LUMINOTECHNIC FEATURES

Luminance C0°G65°: 638

Luminance C90°G65°: 632



UGR

UGR crosswise: 16.0

UGR lengthwise: 15.9

Lampholder	Quantity	Light source power (W)
LED	1	290.7W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	16.0
UGR lengthwise	15.9



### LOGISTICS

