

**Zip****PX-0515-ANT**

Bollard IP65 Zip LED LED LED 3;NA;NAW RGB Urban grey

**TECHNICAL FEATURES**IP65 IK10 

Power (W)-1 : 3W

Power (W)-2 : -

Power (W)-3 : -

Total power consumption of light (W) : 3W

Correlated Colour Temperature (CCT) : TW
RGB-2700-6000K

Dimming protocol : Light For Life

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Polycarbonate

Diffuser finish : Opal

Voltage / frequency : 220-240V/50-60Hz

Power Factor : 0.50

Useful life : 36.000h L70B30

Warranty : 5 Years

Resistant to marine environments : No

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED

Photobiological risk: RG0

Light source: LED

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0

Light source: LED

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0

VENTILATION FEATURES

Power used: 3W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 1.22

Packaged weight (kg): 1.39

Packaging: 1113mm x 113mm x 605mm



4 Un