MTEREB080E30A

# Tero


# **Table**

Tero is a family of pedestals that create a gentle, attractive dialogue between the wood and the steel in surrounding base. A fusion providing a formal, different image, able to live together in different spaces with naturalness and personality.

DESIGNED BY JORGE PENSI



# ondarreta



#### **DIMENSIONS**

Ø70 cm x 75 cm x 72 cm [27.6" x 29.5" x 28.3"] (diameter x height x free height) Ø80 cm x 75 cm x 72 cm [31.5" x 29.5" x 28.3"] (diameter x height x free height) 70 cm x 70 cm x 75 cm x 72 cm [27.6" x 27.6 x 29.5" x 28.3"] (width x depth x height x free height) 80 cm x 80 cm x 75 cm x 72 cm [31.5" x 31.5" x 29.5" x 28.3"] (width x depth x height x free height)

# **WEIGHT**

Ø70 19,5 kg (43 lb) Ø80 21,5 kg (47,4 lb) 70 x 70 21,5 kg (47,4 lb) 80 x 80 24,5 kg (54 lb)

# PACKAGING

Pedestal: 62,5 cm x 58 cm x 99,5 cm (24.6" x 22.8" x 39.2")

Tabletop: Ø70 Box dimensions: 80 cm x 80 cm x 15 cm (31.5" x 31.5" x 5.9")

Ø80 Box dimensions: 90 cm x 90 cm x 15 cm (35.4" x 31.5" x 5.9")

70 x 70 Box dimensions: 80 cm x 80 cm x 15 cm (31.5" x 31.5" x 5.9")

80 x 80 Box dimensions: 90 cm x 90 cm x 15 cm (35.4" x 31.5" x 5.9")

#### **ORIGIN**

100% Made in Europe

# **DESIGN**

Pensi Studio









# **COMPONENTS**

#### **COLUMN**

#### Beech and Oak

10 cm (3.9") side triangular profile column.

#### **Finish**

Stained

#### BASE

#### Material

Base composed by three supports, 45 cm (17.7") diameter and 8 mm (0.3") thick cold laminated St-37 (S-235) quality steel sheet.

#### Technical characteristics:

Tensile Strength: 340-470 N/mm2 (49,300-68,160 psi); Elastic Limit > 235 N/mm2 (32,080 psi); Elongation > 25%, Surface Hardness > 110 HB.

# Finishes

Colour epoxy

#### TABLE TOP SUPPORT

#### Material

29,5 cm (11.6") side and 0,5 cm (0.2") thick cold laminated St-37 quality steel sheet.

#### Finishes

Colour epoxy

# TABLE TOP

#### Material

A variety of beechwood, stratified, compact, compacmel surfaces or Arpa Fénix neo.

# **METAL FINISH**

# **EPOXY**

Powder covering formulated with polyester resins, with good both mechanical and chemical properties, outdoor maximum resistance and noxious compounds free. Electrostatic application and oven curated at 200°C (392°F).

#### Technical characteristics:

Thickness (ISO 2360): between 60 and 90 µm.

Adherence (ISO 2409): Grade: 0 (maximum adherence)