




Circular Inward ø600 Surface


Benedito Design

CD4A-00V9AZDU05

Pendant Circular Inward ø600 Surface LED 31.7W LED warm-white 2700K DALI-2 Black 1264lm



TECHNICAL FEATURES



Total power consumption of light (W) : 38W

Real lumens : 1264

Real lm/W : 33

Correlated Colour Temperature (CCT) : LED warm-white 2700K

Lens / reflector angle : HORIZONTAL 101°

UGR : <=19

Structure material : Aluminium

Structure finish : Black

Diffuser material : Polycarbonate

Diffuser finish : Opal

Smart Compatible

- 71-5961-00-00: Casambi

Driver Brand : MEAN WELL

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : DALI-2

Power Factor : 0.90

Useful life : 50.000h L80B20

Warranty : 5 Years

LUMINOTECHNIC FEATURES

Luminance C0°G65°: 1104

Luminance C90°G65°: 1093



UGR

UGR crosswise: 17.7

UGR lengthwise: 17.6

Lampholder	Quantity	Light source power (W)
LED	1	31.7W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	17.7
UGR lengthwise	17.6



LOGISTICS

Net weight (kg): 3.4

Packaged weight (kg): 5.42

Packaging: 700mm x 700mm x 100mm



LIGHT APPLICATION

