



Model Sheet



Optional : Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

| | |
|---------------|--|
| Finish | <div>42 Blue M1 NCS S 5010-B10G</div> <div>37 Terra Red NCS S 4040-Y70R</div> <div>10 White NCS S 0300-N</div> <div>24 Beige M1 NCS S 2005-Y50R</div> <div>11 Black NCS S 8500N</div> <div>47 Green L1 NCS S 4005-G80Y</div> |
|---------------|--|

| | |
|------------------------------|---|
| LED temperature color | 2700 K |
| Dimming | 1-10V PUSH Optional DALI or Casambi Min. quantity, upcharge and extra lead time apply [EN] |

| | |
|--------------------------|-----------------|
| Installation type | Built-in Canopy |
|--------------------------|-----------------|

| | |
|---------------------|---|
| Materials | Ceiling rose: Steel |
| Light source | 1 x LED 9,3W 350mA E |
| LED | CRI>90 1041 lm 116 2700 K |
| Driver | CC - Constant Current 350 110~240 V 50/60 HZ |
| Remarks | Built-in <div> <div> <div></div> <div></div> </div> <div>Dimmable</div> <div>LED</div> </div> <div> <div>IP20</div> <div>Bi-volt</div> <div>50-60Hz</div> </div> |


| | |
|--------------------|---------------|
| Application | Hanging lamps |
|--------------------|---------------|

| | |
|------------------|--|
| Packaging | 1 Box 0.35 m x 0.35 m x 0.26 m Gross weight 3 Net weight 1.4 Vol. 0.0318 |
|------------------|--|

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Other Applications

