

TECHNICAL CHARACTERISTICS

TCHI2EEA

# Chico


## Stool

Chico; reinterpreting the classics. A stool with a steel structure, combined with a circular seat that can be of wood, laminated or upholstered.

DESIGNED BY ONDARRETA TEAM



**ondarreta**



## DIMENSIONS

H45: 43 cm x 43 cm x 45 cm (16.9" x 16.9" x 17.7") [width x depth x height]

H64: 43 cm x 43 cm x 64 cm x 20 cm (16.9" x 16.9" x 25.2" x 7.9") [width x depth x height x footrest height]

H79: 41 cm x 41 cm x 74 cm x 25 cm (16.1" x 16.1" x 29.1" x 9.8") [width x depth x height x footrest height]

## WEIGHT

H47: 3,1kg (6,63 lb)

H65: 4,5 kg (9,92 lb)

H75: 5,4 kg (11,9 lb)

## PACKAGING

H45 two chair per box, box dimensions:  
44 cm x 43 cm x 92 cm (17.3" x 16.5" x 35.4")

H64 one chair per box, box dimensions:  
44 cm x 43 cm x 79 cm (17.3" x 16.5" x 31.1")

H74 one chair per box, box dimensions:  
44 cm x 43 cm x 92 cm (17.3" x 16.5" x 35.4")

## STACKABILITY

Up to 5 unities in wood version (H45)

## ORIGIN

100% made in Europe

## DESIGN

Ondarreta Team



## **COMPONENTS**

### **FRAME**

#### **Material**

10 x 30mm (0.4" x 1.2") sides 1,5 mm (0.06") thick cold laminated St-37 quality rectangular steel tube.  
Tensile Strength: 340-470 N/mm<sup>2</sup> (49,300-68,160 psi);  
Elastic Limit > 235 N/mm<sup>2</sup> (32,080 psi); Elongation > 25%,  
Surface Hardness > 110 HB.

#### **Finish**

Colour Epoxy

### **SEAT**

#### **Beech**

32 cm (12.6") diameter Beech plywood board shell, 19 mm (0.75") thick. It's made of especially treated sheets, glued, pressed and CNC mechanized.

#### **Fabrics**

30 mm (1.2") thick polyurethane elastic foam and 5 mm (0.2") thick medium density polyether stuffing foam glued at 32 mm (1.2") diameter and 19 mm (0.75") height wood cylinder.

#### **Laminate**

High pressure laminate glued and pressed in high temperatures on a Birch plywood wood table.

#### **Finish**

Stained, lacquered, laminate or fabric.

## **METAL FINISHES**

### **EPOXYS**

Powder covering formulated with polyester resins, with good both mechanical and chemical properties, outdoor maximum resistance and noxious compounds free. Electrostatic application and oven cured at 200°C (392°F).

#### **Technical Characteristics:**

Thickness (ISO 2360): between 60 and 90 µm.

Adherence (ISO 2409): Grade 0 (maximum adherence).

## **WOOD FINISHES**

### **STAIN**

Pigmented enamel with a transparent stain coating. Reactive drying paints: excellent adherence between layers and better mechanical resistance.

#### **Technical Characteristics:**

Satisfying UNE EN 71-3 normative; Formaldehyde free compounds.



## **LACQUER**

Pigmented reactive drying lacquers.

## **Technical Characteristics:**

Satisfying UNE EN 71-3 normative; Formaldehyde free compounds.

## **COM REQUIREMENTS**

For upholstering Chico: 45 cm (17.7") width/unit