Algorithm



0855


Design By Toan Nguyen

Pendant light fitting designed by Toan Nguyen. Composed of a collection of hand blown glass spheres with LED light source suspended at different heights, anchored to the ceiling via a floating tubular structure. Available with ceiling rose or built-in. The finishes are matt graphite and matt white.

Model Sheet







Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish



18 Graphite ADAPTA RF 9913 WX



93 White **RAI 9016**

LED temperature color

2700 K / 3500 K

Dimmina

Push; 1-10V; DALI-2 / Casambi

Instalation type

Surface Canopy

Materials

Sphere: Blown glass Glass fastening: Aluminum Diffuser: PC- Polycarbonate Pendant structure: Steel

Light source

5 x LED 3,15W 1050mA

LED

CRI>80 1562 lm 99 2700 K / 3500 K

Driver

Constant Current 1050 100~240 V V 50~60 Hz HZ

Remarks

Request built-in canopy at www.vibia.com

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the

cables.





IP20 Bi-volt 50-60Hz

Application

Hanging lamps

Packaging

0.552 m x 0.552 m x 0.18 m Gross weigth 8.8

Net weigth 4.75 Vol. 0.0548


Lighting effect


General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data





Efficiency Coordinate System **Total Flux** Maximum Value

49.50% CG 1561.40 lm 141.16 cd/klm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty