



Circular Inward ø2000 Surface


CD4C-00A9AZDU05

Benedito Design

Pendant Circular Inward ø2000 Surface LED 110W LED warm-white 2400K DALI-2 Black 3364lm



TECHNICAL FEATURES



Total power consumption of light (W) : 118.5W

Driver Brand : MEAN WELL

Real lumens : 3364

Voltage / frequency : 100-240V/50-60Hz

Real lm/W : 28

Dimming protocol : DALI-2

Correlated Colour Temperature (CCT) : LED warm-white 2400K

Power Factor : 0.90

Lens / reflector angle : HORIZONTAL 104°

Useful life : 50.000h L80B20

UGR : <=16

Warranty : 5 Years

Structure material : Aluminium


Structure finish : Black

Diffuser material : Polycarbonate

Diffuser finish : Opal

Smart Compatible

- 71-5961-00-00: Casambi



LUMINOTECHNIC FEATURES

Luminance C0°G65°: 248

Luminance C90°G65°: 246



UGR

UGR crosswise: 12.6

UGR lengthwise: 12.6

Lampholder	Quantity	Light source power (W)
LED	1	110W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	12.6
UGR lengthwise	12.6



LOGISTICS

Net weight (kg): 12

Packaged weight (kg): 16

Packaging: 1900mm x 650mm x 150mm



