

Structural


2600

Design By Arik Levy

Wall light with basic lines and cubic volumes that form sculptures integrated into the architecture.

VIBIA

Model Sheet



Finish

15 Grey L2
NCS S 2500-N

21 Black Grey
NCS S 7000-N

LED temperature color

3000 K

Dimming

1-10V

Optional DALI or Casambi
Min. quantity, upcharge and extra lead time apply [EN]

Installation type

Surface Canopy

Materials

Body: Aluminum
Diffuser: Polycarbonate
Profile: Aluminum

LED

CRI>90
3000 K

Driver

CV - Constant Voltage [object
Object] 110~240 V 50/60 HZ

Remarks

Only one main input by square box
16x16cm.



Dimmable

LED

IP20

Bi-volt

50-60Hz

1-10V

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency	100.00%
Coordinate System	CG
Total Flux	176.90 lm
Maximum Value	159.34 cd

Other Applications



Application

Wall Lamps

Packaging

1 Box
0.265 m x 0.265 m x 0.165 m
Gross weight 1.5
Net weight 1.1
Vol. 0.0115

All of our products come with a five-year warranty.
Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com