

Model Sheet

Optional : Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish


-  16 Grey M1
NCS S 4500-N
-  15 Grey L2
NCS S 2500-N
-  37 Terra Red
NCS S 4040-Y70R
-  24 Beige M1
NCS S 2005-Y50R
-  21 Black Grey
NCS S 7000-N
-  10 White
NCS S 0300-N

LED temperature color 2700 K / 3000 K / 3500 K

Dimming DALI / Push; 1-10V; DALI / Casambi

Installation type Remote Micro / Built-in XS / Surface Canopy / Surface Free Wire

Materials LED support: Aluminum
Tube: Steel
Ceiling rose: Steel

LED  CRI>90 2900 lm 145
2700 K / 3000 K / 3500 K

Driver Constant Current 700 110~240
V V 50~60 Hz HZ

  **Dimmable** **LED**
IP20 **Bi-volt** **50-60Hz**

Application Hanging lamps

Packaging 1 Box
0.94 m x 0.31 m x 0.205 m
Gross weight 4.2
Net weight 1.55
Vol. 0.0597

Lighting effect

General lighting

Lamp for general lighting that equally distributes the light in all directions.

Photometric Data

Efficiency 48.13 lm/W
Coordinate System CG
Total Flux 1169.89 lm
Maximum Value 433.69 cd