

Design By Ramos & Bassols

The Spa wall or ceiling lamp is suitable for damp areas. Its versatile system enables the luminaries to be placed in a line to illuminate up to six metres of wall or ceiling space.

Model Sheet

Finish 23 Warm White
NCS S 0502-Y50R

11 Black
NCS S 8500-N

25 Beige D1
NCS S 4005-Y50R

LED temperature color 2700 K / 3500 K

Dimming DALI / 1-10V

Materials Body: Aluminum
Diffuser: PMMA
Ceiling rose: Aluminum

Light source 2 x LED STRIP 32,4W 600mA



LED CRI>90 9637 lm 138
2700 K / 3500 K

Driver Constant Current 600
220~240 V V 50~60 Hz HZ



Dimmable

LED

50-60Hz



1-10V

Application Ceiling Lamps

Packaging 3 Box
3.3 m x 0.1 m x 0.1 m
Gross weight 12.5
Net weight 7.6
Vol. 0.0749

Lighting effect

Linear

Linear lighting applications for functional and graphic illumination

Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency 60.77 lm/W

Coordinate System CG

Total Flux 3215.95 lm

Maximum Value 1373.33 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com