



Bind solo

6654



VIBIA





Bind Solo provides direct down lighting, offering perfect integration within its surrounding architecture as it is completely recessed.

Model Sheet



Ø 4 cm

Finish	 04 Black NCS S 8500N
	 24 Beige M1 test ral
LED temperature color	2700 K / 3000 K / 3500 K / Tunable White
Dimming	PUSH DALI / CASAMBI / NO DRIVER / On/Off
Installation type	Remote driver Built-in Micro

Materials	Body: Aluminum Optics: PC- Polycarbonate
Light source	1 x undefined 
LED	CRi>90 530 lm 101,9 2700 K / 3000 K / 3500 K / Tunable White
Driver	Constant Current 300 220~240 V V 50~60 Hz HZ   IP20 

Application Ceiling Lamps

Packaging 1 Box
0.15 m x 0.15 m x 0.075 m
Gross weight 0.68
Net weight 0.2
Vol. 0.0016

Lighting effect

Accent

Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances



Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com