




Ringo Ø155mm



PX-0355-INO

Recessed uplighting IP65/IP67 Ringo Ø155mm LED 9.1W 3000K Stainless steel 632lm

TECHNICAL FEATURES



IP65/IP67 IK04



Power (W) : 9.1W

Total power consumption of light (W) : 10.1W

Real lumens : 632

Real lm/W : 63

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Dimming protocol : ON-OFF

Lens / reflector angle : SPOT 19°

UGR : <= 16

Structure material : Stainless steel AISI304

Structure finish : Stainless steel

Diffuser material : Glass

Diffuser finish : Transparent

Voltage / frequency : 100-240V/50-60Hz

Useful life : 36.000h L70B30

Warranty : 5 Years

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED

Luminance C0°65°: 1974

Luminance 90°65°: 1977

CRI: 80

MacAdam steps: 3



Photobiological risk: RG0

UGR

UGR crosswise: 10.7

UGR lengthwise: 10.7

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	10.7
UGR lengthwise	10.7



VENTILATION FEATURES

Power used: 10.1W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 1.02

Packaged weight (kg): 1.13

Packaging: 185mm x 185mm x 120mm



