




MINI-COLIN is a minimalist recessed light. Its body fully integrates into the space and it provides effective lighting. A Colour Rendering Index of 95 provides a realistic rendering of the colour. The higher the value, the better the human eye perceives the real colour of the objects it lights. With a heat temperature of 4000K, this downlight lamp is suitable for lighting work spaces. The 56° version is perfect for lighting in restaurants and hotels, and also in exhibition rooms or museums.



General characteristics

| | |
|------------------------|-----------|
| Type | III |
| IP | 23 |
| Horizontal orientation | ☺ 20 |
| Power | 48W |
| Cutting size | 263x129mm |

Material

| | |
|----------------|-----------|
| Body/Structure | Aluminium |
|----------------|-----------|

Finish

| | |
|----------------|-------|
| Body/Structure | Black |
|----------------|-------|

Lighting characteristics

| | |
|---------------------------|----------------|
| Light source included | |
| Maximum ceiling thickness | 30 |
| Light source | COB LED |
| Temperature | 4000K |
| MacAdam Steps | 2 SDCM |
| LM | 3900Lm |
| CRI | 95 |
| LED lifetime | 80000H L90/B10 |
| Dimmable light source | SI |
| Degrees of light aperture | 56 |
| Light direction | ACENTO |

Driver

| | |
|----------------------------|----------|
| Requires Driver | SI |
| Driver embedded | NO |
| Maximum driver information | 700mA CC |

File download

| | |
|-------------------|------------|
| General documents | Download > |
| Images | Download > |
| 2D / 3D | Download > |

