



Model Sheet




Optional : Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish	93 White RAL 9016
	18 Graphite ADAPTA RF 9913 WX
LED temperature color	2700 K / 3500 K
Dimming	Push; 1-10V; DALI-2 / Casambi
Installation type	Built-in
Materials	Sphere: Blown glass Glass fastening: Aluminum Diffuser: PC- Polycarbonate Pendant structure: Steel
Light source	12 x LED 3,15W 1050mA F
LED	CRI>80 3748 lm 99 2700 K / 3500 K
Driver	Constant Current 1050 100~240 V V 50~60 Hz HZ
Remarks	The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the cables.
	<div> <div> <div></div> <div>F</div> <div>Dimmable</div> <div>LED</div> </div> <div> <div>IP20</div> <div>Bi-volt</div> <div>50-60Hz</div> </div> </div>
Application	Hanging lamps
Packaging	2 Box 1.089 m x 1.089 m x 0.18 m Gross weight 16.5 Net weight 11.4 Vol. 0.336

Lighting effect

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency	49.49%
Coordinate System	CG
Total Flux	3747 lm
Maximum Value	141.79 cd/klm

Other Applications

