



Bind solo

6650

VIBIA

Bind Solo provides direct down lighting, offering perfect integration within its surrounding architecture as it is completely recessed.

Model Sheet



Ø 4 cm

Finish	 04 Black NCS S 8500N
	 24 Beige M1 test ral
LED temperature color	3000 K / 3500 K
Dimming	PUSH DALI / On/Off / NO DRIVER / CASAMBI
Installation type	Remote driver Built-in Micro


Materials Body: Aluminum
Optics: PMMA- Methacrylate

Light source 1 x undefined



LED CRI>90 530 lm 101,9
3000 K / 3500 K

Driver Constant Current 300
220~240 V V 50~60 Hz HZ



Application Ceiling Lamps

Packaging 1 Box
0.15 m x 0.15 m x 0.075 m
Gross weighth 0.68
Net weighth 0.2
Vol. 0.0016

Lighting effect

Accent

Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances



Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com