



Dual

PX-0514-ANT

Wall fixture IP65 Dual LED LED LED 4;NA;NAW RGB Urban grey

TECHNICAL FEATURES

IP65 IK10



Power (W)-1 : 4W

Power (W)-2 : -

Power (W)-3 : -

Total power consumption of light (W) : 4W

Correlated Colour Temperature (CCT) : TW
RGB-2700-6000K

Dimming protocol : Light For Life

Structure material : Polycarbonate + ABS

Structure finish : Urban grey

Diffuser material : Polycarbonate

Diffuser finish : Tinted

Voltage / frequency : 220-240V/50-60Hz

Power Factor : 0.50

Useful life : 36.000h L70B30

Warranty : 5 Years

Resistant to marine environments : No

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED

Photobiological risk: RG0

Light source: LED

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0

Light source: LED

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0

VENTILATION FEATURES

Power used: 4W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 0.3

Packaged weight (kg): 0.36

Packaging: 225mm x 55mm x 118mm



12 Un